

S3C TRAILER



KEY FEATURES/BENEFITS

RUGGED DESIGN

Featuring rugged, customer-driven advancements, the S3C trailer is designed specifically for Ditch Witch® pedestrian trenchers, and the VP30 vibratory plow.

RAIL SYSTEM

Features a new rail system for easier loading and unloading.

HIGHER LOAD CAPACITY

The S3C trailer can haul equipment up to 3,500 lbs—a 52 percent capacity increase at a lower price point than its predecessor.

SAFETY FEATURES

The trailer is equipped with standard tie-down points, tongue safety chains, complete lighting, a custom wiring harness and clearance lights for highway driving.

UNIVERSAL MOUNTING KIT

Universal mounting kit with one attachment point eliminates the need for more chains and binders, ideal for any CX-series trencher, RT model or VP30 vibratory plow.

IMPROVED DURABILITY

The S3C features 16-inch wheels and highway-rated tires for improved durability and safety at highway speeds.

INTRODUCING THE
S3C
TRAILER



S3C TRAILER SPECIFICATIONS

DIMENSIONS

| | U.S. | METRIC |
|---------------|-------------|--------------|
| D | 38 in | 965 mm |
| D2 | 70 in | 1.8 m |
| L | 133 in | 3.4 m |
| L2 | 122 in | 3.1 m |
| H | 8.5-22.5 in | 216-571.5 mm |
| H2 | 17.6 in | 447 mm |
| H3 | 13.6 in | 345.4 mm |
| W | 64.2 in | 1.6 m |
| W2 | 42.8 in | 1.1 m |
| W3 | 10 in | 254 mm |
| Loading Angle | 15° | |

RUNNING GEAR

| | |
|-------|---|
| Axles | 3,500 lb rated Dexter 4" drop, leaf spring axle |
|-------|---|

TIRE PRESSURE

| | |
|-----------|-------------------|
| Tire size | ST205/7R15,C |
| Inflation | 50 psi 345 kPa |

LOAD RATINGS

| | | |
|-------------------|-----------|---------|
| GVWR | 2,990 lbs | 1356 kg |
| GAWR | 3,500 lbs | 1588 kg |
| Tare Weight | 643 lbs | 292 kg |
| Tongue load, max. | 450 lbs | 204 kg |
| Cargo, max. | 2,300 lbs | 1043 kg |
| Number of axles | 1 | |
| Brakes | n/a | |
| Electrical system | 12 volt | |

COUPLER OPTIONS

| |
|-----------------|
| 2" ball coupler |
|-----------------|

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

