

FT5
FLUID MANAGEMENT

KEY FEATURES/BENEFITS

SUPPORTS SMALLER SYSTEMS
The compact FT5 makes short work of the mixing process. Designed to support smaller HDD systems, the FT5 also supports your need to get the job done right and right on time.

FASTER MIXING
Venturi wet hopper allows excellent mixing of fluids; the hopper's steeper sides help speed up mixing cycles.

EASIER TRANSPORT
Narrow tank can be positioned side-by-side with a drill unit on a trailer, making the equipment easy to transport to the jobsite.

HIGH CAPACITY TANK
200-gallon (757-L) capacity is large enough to get the job done, and just the right size for transporting on small truck or trailer configurations.

VARIETY OF SETUPS
Simplicity of design and multiple configuration options accommodate a variety of setups.

SUPERIOR SUPPORT
Your Ditch Witch equipment is backed by a worldwide network of dealers you can count on for unmatched commitment to your success. From genuine Ditch Witch parts to factory-trained service to expert advice, your Ditch Witch dealer has it all for you.

	U.S.	METRIC
DIMENSIONS		
Length	73 in	1.85 m
Length, w/hose and valve	84 in	2.13 m
Width	32 in	813 mm
Height	53.5 in	1.36 m
Weight, empty	402 lb	182 kg
Weight, full of water	2,071 lb	939 kg
FLUID/MIXING SYSTEM		
Drilling fluid/mixing tank capacity	200 gal	760 L
Flow rate to drilling unit, max	18 gpm	68 l/min

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

	U.S.	METRIC
POWER		
Engine	Honda® GX160	
Fuel	Gasoline	
Cooling medium	Air	
Number of cylinders	1	
Displacement	9.9 in^3	162 cm^3
Bore	2.7 in	69 mm
Stroke	1.8 in	46 mm
Gross power @ 3,600 rpm	5.5 hp	4.1 kW
FLUID CAPACITIES		
Fuel tank	1 gal	3.6 L
Engine oil	0.6 qt	0.6 L

Ditch Witch®

©2019 The Charles Machine Works, Inc.