S3C TRAILER



FEATURES & BENEFITS

RUGGED DESIGN

Featuring rugged, customer-driven advancements, the S3C trailer is designed specifically for Ditch Witch® pedestiran trenchers, and the VP30 vibratory plow.

RAIL SYSTEM

Features a new rail system for easier loading and unloading.

HIGHER LOAD CAPACITY

The S3C trailer can haul equipment up to 3,500 lbs—a 52 percent capacity increase at a lower price point than its predecessor.

SAFETY FEATURES

The trailer is equipped with standard tie-down points, tongue safety chains, complete lighting, a custom wiring harness and clearance lights for highway driving.

UNIVERSAL MOUNTING KIT

Universal mounting kit with one attachment point eliminates the need for more chains and binders, ideal for any CX-series trencher, RT model or VP30 vibratory plow.

IMPROVED DURABILITY

The S3C features 16-inch wheels and highway-rated tires for improved durability and safety at highway speeds.

S3C TRAILER SPECIFICATIONS

DIMENSIONS	U.S.	METRIC
D	38 in	965 mm
D2	70 in	1.8 m
L	133 in	3.4 m
L2	122 in	3.1 m
H	8.5-22.5 in	216-571.5 mm
H2	17.6 in	447 mm
H3	13.6 in	345.4 mm
W	64.2 in	1.6 m
W2	42.8 in	1.1 m
W3	10 in	254 mm
Loading Angle	15°	

RUNNING GEAR

Axles	3,500 lb rated Dexter 4" drop, leaf spring axle

TIRE PRESSURE	U.S.	METRIC
Tire size	ST205/7R15,C	
Inflation	50 psi	345 kPa


LOAD RATINGS

GVWR	2,990 lbs	1356 kg
GAWR	3,500 lbs	1588 kg
Tare Weight	643 lbs	292 kg
Tongue load, max.	450 lbs	204 kg
Cargo, max.	2,300 lbs	1043 kg
Number of axles	1	
Brakes	n/a	
Electrical system	12 volt	

COUPLER OPTIONS

2" ball coupler

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.



©2020 The Charles Machine Works, Inc.